

UNITED STATES PATENT APPLICATION

OF

SUK WON CHOI,

SU SEOK CHOI,

JANG JIN YOO

AND

MOO JONG LIM

FOR

FERROELECTRIC LIQUID CRYSTAL DISPLAY

AND METHOD OF DRIVING THE SAME

LONG ALDRIDGE & NORMAN, LLP
701 PENNSYLVANIA AVENUE, N.W.
SUITE 600
WASHINGTON, DC 20004
TEL: 202/624-1200
FAX: 202/624-1298

[0001] This application claims the benefit of Korean Patent Application No. 2000-85287, filed on December 29, 2000, the entirety of which is hereby incorporated by reference for all purposes as if fully set forth herein.

BACKGROUND OF THE INVENTION

Field of the Invention

[0002] This invention relates to a ferroelectric liquid crystal display, and more particularly to a ferroelectric liquid crystal display and a driving method that is capable of preventing deterioration of light efficiency caused by a low voltage holding ratio.

Description of the Related Art

[0003] Generally, a liquid crystal display (LCD) controls light in accordance with a liquid crystal alignment state to thereby display a desired picture on a screen. A liquid crystal used for such a LCD is in a neutral phase between a liquid state and a solid state, thereby having both a fluidity and an elasticity. In a thermodynamic phase transition process of the liquid crystal, for example, a liquid crystal having a smectic C phase is rotated along a smectic layer, taking a layer structure having the same electrical and magnetic property. The smectic C phase liquid crystal is rotated along an outer line of a virtual cone.

[0004] The smectic C phase liquid crystal has a characteristic of making a spontaneous polarization irrespectively of an external electric field. This type of liquid crystal is usually referred to as ferroelectric liquid crystal (FLC). The FLC has been actively studied because it has a fast response speed as a result of its spontaneous polarization characteristic. Accordingly, it has an ability to realize a wide viewing angle without a special electrode structure and a compensating film. In addition, the FLC includes a deformed helix FLC mode, a surface stabilized FLC mode, an anti-FLC mode, a V-type FLC mode and a half V-type FLC mode, etc. The V-type FLC mode and the half V-

type FLC mode modes will be described.

[0005] Fig. 1 shows an alignment state of a liquid crystal cell in the V-type FLC mode.

[0006] Referring to Fig. 1, the liquid crystal cell, in the V-type FLC mode, includes
5 an upper substrate 1 on which a common electrode 3 and an alignment film 5 are disposed, a
lower substrate 11 on which a TFT array 9 including a pixel electrode and an alignment film
7, and a liquid crystal 13 injected between the upper and lower substrates 1 and 11. The
alignment films 5 and 7 are aligned into a desired state by a rubbing method. The injected
liquid crystal 13 forms a smectic layer, taking a layer structure, and is arranged into a phase
10 having a desired slope with respect to a plane perpendicular to the smectic layer. The liquid
crystal 13 has a desired inclination angle with respect to an aligned direction of the alignment
film and is aligned such that the adjacent smectic layers have opposite polarities with respect
to each other.

[0007] A transmissivity according to a voltage of the V-type FLC mode liquid crystal
15 cell is shown in Fig. 2. The liquid crystal 13 within the V-type FLC mode liquid crystal cell
responds to positive and negative voltages applied thereto. Since the transmissivity is
suddenly changed according to an application of the positive and negative voltages, a
transmissivity curve according to a voltage has a V shape. As shown in Fig. 2,
transmissivity is increased as a positive voltage increases, whereas transmissivity is
20 decreased as a negative voltage increases.

[0008] Fig. 3 shows an alignment state of a liquid crystal cell in the half V-type FLC mode.

[0009] In Fig. 3, a liquid crystal 15 within the half V-type FLC mode liquid crystal
cell injected between the upper substrate 1 and the lower substrate 11 forms a smectic layer
25 taking a layer structure. The liquid crystal 15 is aligned at a desired inclination angle with

respect to an alignment treatment direction of the alignment films 5 and 7 such that the adjacent smectic layers have a different polarity, unlike the liquid crystal 13 in the V-type FLC mode. A half V-type mode liquid crystal can be implemented by applying a positive or negative electric field in advance while at the same time lowering its temperature into a temperature having a smectic phase. The half V-type FLC mode liquid crystal 15 formed in this manner responds to only one of the applied positive and negative voltages. Thus, as seen from Fig. 4, a transmittance curve according to a voltage of a liquid crystal cell in the half V-type FLC mode has a half V shape. A T-V characteristic in Fig. 4 represents the situation when a negative voltage is used to make an initial uniform alignment. In this case, transmissivity is almost not increased upon application of a negative voltage, whereas it is increased in accordance with an increase in a positive voltage. The opposite is true when a positive voltage is used to make an initial uniform alignment, that is, transmissivity is increased in accordance with an increase in a negative voltage.

[0010] A thermodynamic phase transition process of the half V-type FLC mode liquid crystal 15 is as follows:

Isotropic nematic (N*) phase → smectic C* (Sm C*) phase crystal

[0011] As the temperature gradually decreases, the phase transition process of a liquid crystal goes from left to right as shown in the above thermodynamic phase transition.

[0012] For example, the liquid crystal 15 is aligned in parallel to a rubbing direction, when its temperature is slowly lowered to reach a temperature having a nematic phase after the liquid crystal 15 is injected into the liquid crystal cell at a temperature having an isotropic phase. If an electric field is applied to the interior of the cell while the temperature is slowly lowered, the liquid crystal 15 is phase-changed into a smectic phase. The direction of a spontaneous polarization of the liquid crystal 15 generated at this time is arranged in such a manner to be consistent with that of an electric field formed at the interior of the cell.

As a result, when the liquid crystal 15 within the liquid crystal cell is subjected to a parallel alignment treatment, it takes a molecule arrangement in the spontaneous polarization direction, which is consistent with the direction of an electric field applied in said phase transition process of two possible molecule arrangement directions, thereby having a uniform alignment state.

[0013] Molecular arrangement in the spontaneous polarization direction will be described in detail with reference to Fig. 5 and Fig. 6 below. First, as seen from Fig. 5, if a negative electric field $E(-)$ is applied to the alignment of the liquid crystal 15, then a spontaneous polarization direction of the liquid crystal 15 that is identical to the electric field direction is made, thus providing a uniform alignment. In the liquid crystal cell, as shown in Fig. 6, a liquid crystal arrangement is changed upon application of a positive electric field $E(+)$, while a liquid crystal arrangement is not changed upon application of a negative electric field $E(-)$. In order to utilize a response characteristic to an electric field of the liquid crystal 15, polarizers perpendicular to each other are arranged at the upper and lower portions of the liquid crystal cell. At this time, a transmission axis of one polarizer is arranged to be consistent with an initial liquid crystal alignment direction. In the liquid crystal cell having the above-mentioned arrangement, a transmission curve according to a voltage application has a half V shape as shown in Fig. 4 experimentally.

[0014] With respect to a negative electric field $E(-)$, a liquid crystal arrangement is not changed to shut out a light. Otherwise, with respect to a positive electric field $E(+)$, a liquid crystal arrangement is changed to transmit light. In this case, as a positive electric field $E(+)$ increases, a transmittance also is increased.

[0015] Referring to Fig. 7, the ferroelectric LCD includes an upper substrate 102 on which a color filter array 104, a common electrode 106 and an alignment film 107 that has undergone an alignment treatment are sequentially disposed. A lower substrate 114, on

which a pixel electrode 112 including a TFT array, and an alignment film 110 that has undergone an alignment treatment are sequentially disposed. Spacers (not shown) are provided between the upper substrate 102 and the lower substrate 114. Ferroelectric liquid crystals 108 are injected into an inner space between the upper and lower substrate 102 and 114 defined by the spacers. Polarizers 100 and 120 are attached at the outsides of the upper and lower substrates 102 and 114. A backlight 116 for irradiating a light and a backlight driver (not shown) for controlling a turn-on of the backlight 116 are provided.

[0016] The backlight driver applies an electrical signal to the backlight 116 to generate light. The backlight 116 creates a white light in response to the electrical signal from the backlight driver. The light generated from the backlight 116 is converted into a surface light source to be applied uniformly incident to the liquid crystal display panel. The white light from the backlight 116 is transmitted or blocked depending on an alignment state of the ferroelectric liquid crystals 108. For example, a voltage is applied to a certain pixel to generate a voltage difference between a pixel electrode 112 and a common electrode 106. Accordingly, a rotation angle of the liquid crystal molecules is changed and a transmittance is controlled in accordance with the changed rotation angle of the liquid crystal molecules, thereby implementing various black and white gray scales.

[0017] The light generated from such a backlight 116 transits the red, green and blue color filters 104 on the upper substrate 102 to have saturation and brightness. As illustrated in Fig. 8, one pixel has 3 sub-pixels for realizing a picture. The each sub-pixel corresponds to the pixel cell to sequentially form the red, green, blue color filter 104. The color filter 104 selectively transmits the red, green and blue wavelength corresponding to the specific wavelength of the white light to realize the colorful picture. The black matrix 118 is built between each of color filters 104 for each color not to interfere.

[0018] In the meantime, Fig. 9 shows the characteristics of the voltage holding ratio

(VHR) of a ferroelectric liquid crystal. VHR refers to the ratio of holding the voltage charge in a liquid crystal cell after a voltage is applied to the liquid crystal cell. In other words, because the driving voltage is not applied to the liquid crystal cell during the non-selected period of LCD driving, the liquid crystal cell holds a floating state. The electric charge that is charged in the liquid crystal cell during the selected period upon the application of the driving voltage, is discharged to the outside of the liquid crystal cell during the non-selected period. VHR refers to the degree of the liquid crystal cell sustaining the voltage charge in the floating state. VHR characteristics of the ferroelectric liquid crystal is described as follows.

[0019] The ferroelectric liquid crystal has the characteristics of the spontaneous polarization, i.e., it has a polarity when a driving voltage is not applied. Thus, it rapidly restores the elasticity after the driving voltage has been applied. The ferroelectric liquid crystal is rotated to the position where the light is transmitted by the driving voltage initially supplied. However, the voltage charged to the ferroelectric liquid crystal drops below 50% of the voltage charge initially supplied in accordance with the characteristics of the depolarization of the liquid crystal. The voltage decreased is sustained for one frame period. The ferroelectric liquid crystal is rotated to the position where light is not transmitted by such a voltage decrease. Consequently, the time sustaining the position of the liquid crystal molecule transmitting the light, becomes less for the brightness to drop.

[0020] As a method for improving the VHR characteristics of the ferroelectric liquid crystal, the storage capacitance in the TFT design has been increased.

[0021] Fig. 10 shows the relationship of the VHR and the aperture ratio according to the storage capacitance (Cst).

[0022] Referring to Fig. 10, the VHR increases but the aperture ratio decreases when the size of the storage capacitance increases. In other words, when the size of the storage

capacitor is increased to increase the value of the storage capacitance, the size of storage capacitor affects the pixel area to which the light is transmitted to thereby reduce the aperture ratio.

[0023] Accordingly, there is a limitation in the indefinite increase of the storage capacitance size to improve the VHR characteristics.

[0024] Also, decreasing the size of spontaneous polarization of the ferroelectric liquid crystal has been used as another way to improve the VHR characteristics of the ferroelectric liquid crystal.

[0025] Fig. 11 shows the relationship according to the spontaneous polarization of the ferroelectric liquid crystal.

[0026] Referring to Fig. 11, the VHR decreases when the spontaneous polarization increases. In other words, the VHR characteristics can be improved by decreasing the spontaneous polarization of the ferroelectric liquid crystal. However, the response time of the ferroelectric liquid crystal described in the Equation 1 should be considered when changing the size of the spontaneous polarization of the ferroelectric liquid crystal for the improvement of the characteristics of the VHR.

$$\tau = \gamma / (P * E)$$

[Equation 1]

[0027] In Equation 1, τ is the response time of the liquid crystal, γ is the rotational viscosity of the liquid crystal, P is the spontaneous polarization of the liquid crystal, E is the electric field.

[0028] As shown in the Equation 1, the response time of the ferroelectric liquid crystal has an inverse proportional relationship with the size of the spontaneous polarization of the ferroelectric liquid crystal. In other words, the response time of the ferroelectric

liquid crystal decreases when the degree of the spontaneous polarization increases in the ferroelectric liquid crystal. An increase in VHR results in an increase in the leakage of the voltage charged to the liquid crystal. Whereas, the VHR decreases when the degree of the spontaneous polarization of the ferroelectric liquid crystal increases, and the response time of the ferroelectric liquid crystal increases. Therefore, when the size of the spontaneous polarization of the ferroelectric liquid crystal decreases the response time of the ferroelectric liquid crystal should also be considered.

SUMMARY OF THE INVENTION

[0029] Accordingly, the present invention is directed to ferroelectric liquid crystal display and a driving method thereof that substantially obviates one or more of the problems due to limitations and disadvantages of the related art.

[0030] It is an advantage of the present invention to provide a ferroelectric liquid crystal display and a driving method thereof that is capable of improving light efficiency by preventing the light efficiency deterioration that results from a low voltage holding ratio.

[0031] Additional features and advantages of the invention will be set forth in the description which follows, and in part will be apparent from the description, or may be learned by practice of the invention. The objectives and other advantages of the invention will be realized and attained by the structure particularly pointed out in the written description and claims hereof as well as the appended drawings.

[0032] In order to achieve these and other advantages of the invention, a ferroelectric liquid crystal display according to one aspect of the present invention includes a liquid crystal panel in which a liquid crystal cell is formed at the intersection of the gate line and data line; a data processor for supplying red, green and blue data signals to each of liquid crystal cells; and a backlight that stands by during the responding period of the liquid crystal

after the supplying period of the red, green and blue data signals and sequentially generates red, green and blue lights corresponding to the red, green and blue data signals.

[0033] The liquid crystal panel includes a upper substrate on which a common electrode and an alignment film are sequentially disposed; a lower substrate on which a thin film transistor array, a pixel electrode and an alignment film are sequentially disposed, and a
5 ferroelectric liquid crystal injected between the upper substrate and the lower substrate.

[0034] The backlight includes a backlight driver for supplying an electrical signal to generate the red, green and blue lights, and a backlight controller supplying a control signal to generate the red, green and blue lights for a frame period.

[0035] The ferroelectric liquid crystal responds to the color data signal after the color data signal is supplied to the liquid crystal cell.

[0036] In another aspect of the present invention, a method of driving a ferroelectric liquid crystal display includes sequentially supplying the red, green and blue data signals to a liquid crystal cell formed at the intersection of the gate line and the data line of the liquid
10 crystal panel; the liquid crystal supplying the red, green and blue data signals; and
15 sequentially generating the red, green and blue lights corresponding to each of the red, green and blue data signals after the responding period of the liquid crystal panel.

[0037] The backlight is in a stand-by state during the responding period of the liquid crystal.

[0038] The red, green and blue data signals sequentially are supplied to each of the
20 liquid crystal cells at least once or more during a frame period.

[0039] During a frame period, the red light is irradiated after the red data signal is supplied to the liquid crystal cell, the green light is irradiated after the green data signal is supplied to the liquid crystal cell, and the blue light is irradiated after the blue data signal is
25 supplied to the liquid crystal cell.

BRIEF DESCRIPTION OF THE DRAWINGS

[0040] The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and together with the description serve to explain the principles of the invention.

[0041] In the drawings:

[0042] These and other objects of the invention will be apparent from the following detailed description of the embodiments of the present invention with reference to the accompanying drawings, in which:

[0043] Fig. 1 illustrates an alignment state of a liquid crystal cell in a conventional V-type FLC mode;

[0044] Fig. 2 is a graph representing a transmittance according to a voltage of the conventional V-type FLC mode liquid crystal cell;

[0045] Fig. 3 illustrates an alignment state of a liquid crystal cell in a conventional half V-type FLC mode;

[0046] Fig. 4 is a graph representing a transmittance according to a voltage of the conventional half V-type FLC mode liquid crystal cell;

[0047] Fig. 5 illustrates a method of applying an electric field to implement the conventional half V-type FLC mode liquid crystal cell;

[0048] Fig. 6 depicts a motion of a liquid crystal upon application of a voltage to the conventional half V-type FLC mode liquid crystal cell;

[0049] Fig. 7 is a sectional view of the conventional ferroelectric liquid crystal.

[0050] Fig. 8 illustrates the color filter arrangement of the conventional ferroelectric liquid crystal cell shown in Fig. 7.

[0051] Fig. 9 is a graph representing the characteristics of the voltage holding ratio (VHR) of the conventional ferroelectric liquid crystal shown in Fig. 7.

[0052] Fig. 10 is a graph representing the characteristics of the VHR and the aperture ratio according to the storage capacitance.

5 [0053] Fig. 11 is a graph representing the relationship of the VHR according to the spontaneous polarization of the ferroelectric liquid crystal.

[0054] Fig. 12 illustrates the ferroelectric liquid crystal in accordance with an embodiment of the present invention.

[0055] Fig. 13 is a sectional view of the liquid crystal panel shown in Fig. 12.

10 [0056] Fig. 14 illustrates the driving method of the ferroelectric liquid crystal display shown in Fig. 12.

[0057] Fig. 15 illustrates the liquid crystal cell shown in Fig. 12.

DETAILED DESCRIPTION OF THE ILLUSTRATED EMBODIMENT

15 [0058] Reference will now be made in detail to an embodiment of the present invention, example of which is illustrated in the accompanying drawings.

[0059] Fig. 12 to 15 illustrate the ferroelectric liquid crystal display and the driving method thereof according to an embodiment of the present invention.

20 [0060] Referring to Fig. 12, the ferroelectric liquid crystal display according to the present invention includes a liquid crystal panel 200, a data driver 202 for supplying a data signal to the liquid crystal panel 200, a gate driver 204 for supplying a scanning signal to the liquid crystal panel 200, a timing controller 208 for supplying the data signal and a control signal to the data driver 202 and a scanning control signal to the gate driver 204, a backlight 210 for irradiating light to the liquid crystal panel 200, a light source driver 206 for driving
25 the backlight 210 sequentially, and a light source controller 211 for controlling the light

source driver 206.

[0061] The liquid crystal panel 200, as shown Fig. 13, includes a upper substrate 214 on which a common electrode 216 and an alignment film 218 that has undergone an alignment treatment are sequentially disposed; a lower substrate 226 on which a pixel electrode 224 including a TFT array and an alignment film 222 that has undergone an alignment treatment are sequentially disposed; spacers (not shown) provided between the upper substrate 214 and the lower substrate 226; ferroelectric liquid crystal 220 injected into an inner space defined by the spacers between the upper and lower substrate 214 and 226, and polarizers 212 and 228 attached at the outsides of the upper and lower substrates 214 and 226.

[0062] The liquid crystal panel 200 also includes liquid crystal cells arranged in a matrix configuration on the lower substrate 226, and thin film transistors (TFTs) as switching elements, which are formed at the crossing area of a plurality gate lines (GL) and a plurality data lines (DL) to switch the data signal supplied to the liquid crystal cell.

[0063] Referring again to Fig. 12, the data driver 202 supplies data signals (RGB Data) to the liquid crystal panel 200 corresponding to the control signals inputted from the timing controller 208.

[0064] The gate driver 204, in correspondence with the gate signals inputted from the timing controller 208, controls the on/off state of the gate terminal of the TFTs arranged on the liquid crystal panel 200 line by line to have the data signals supplied from the data driver 202 applied to each of the pixels connected to each of the TFT.

[0065] The data signals, control signals, an input clock, horizontal synchronization signals, a vertical synchronization signals, and a data enable signals, are inputted from an interface not shown in the drawing are supplied to the timing controller 208.

[0066] The timing controller 208 supplies the data signals (RGB Data) and the data

enable signals to the data driver 202. The timing controller 208 also receive the horizontal synchronization signals (H) and the vertical synchronization signals (V) and generate a gate start clock (GSC) and a gate scanning pulse (GSP) to supply to the gate driver 204.

[0067] In this way, the scanning signals supplied from the gate driver 204 turn on the TFT to supply the data signals (RGB Data) supplied from the data driver 202 to the liquid crystal cells. Accordingly, the arrangement state of the liquid-crystal molecule is set in the liquid crystal cell corresponding to the voltage of the data signal (RGB Data) supplied. The light transmitted is controlled according to the arrangement state of the liquid crystal molecule and is synchronized with the data signal by the backlight 210.

[0068] The backlight 210 includes red, green and blue light sources 210R, 210G and 210B. The brightness of the backlight 210 is determined. The red, green and blue light sources 210R, 210G and 210B are sequentially turned on and off by the control signal supplied from the backlight controller 211.

[0069] The ferroelectric liquid crystal display is described in detail as following in connection with the drawing of the timing of the sequential driving as illustrated in Fig. 14.

[0070] Referring to Fig. 14, one frame period of the liquid crystal panel 200 includes the TFT scanning time t_{TFT} of the red, green and blue data signals supplied to the liquid crystal cell, the response time t_{LC} of the liquid crystal corresponding to the red, green and blue data signals, and the time t_{BL} of irradiating the red, green and blue lights.

[0071] The red data signal is supplied to the liquid crystal cell at the TFT scanning time t_{TFT} . Accordingly, the ferroelectric liquid crystal is arranged corresponding to the red data signal. For example, the ferroelectric liquid crystal is arranged in response to the red data signal so that red light is irradiated to the liquid crystal panel 200. Because the ferroelectric liquid crystal rapidly discharges the charged voltage due to the VHR characteristics, red light is irradiated in synchronization with the short time of sustaining the

on-state of the ferroelectric liquid crystal.

[0072] The green data signal is supplied to the liquid crystal cell at the TFT scanning time t_{TFT} . Accordingly, the ferroelectric liquid crystal is arranged corresponding to the green data signal. For example, the ferroelectric liquid crystal arranged in response to the green data signal so that green light is irradiated to the liquid crystal panel 200. Because the ferroelectric liquid crystal rapidly discharges the charged voltage due to the VHR characteristics, green light is irradiated in synchronization with the short time of sustaining the on-state of the ferroelectric liquid crystal.

[0073] The blue data signal is supplied to the liquid crystal cell at the TFT scanning time t_{TFT} . Accordingly, the ferroelectric liquid crystal is arranged corresponding to the blue data signal. For example, the ferroelectric liquid crystal arranged in response to the blue data signal so that blue light is irradiated to the liquid crystal panel 200. Because the ferroelectric liquid crystal rapidly discharges the charged voltage due to the VHR characteristics, the blue light is irradiated in synchronization with the short time of sustaining the on-state of the ferroelectric liquid crystal.

[0074] The tri-color light is sequentially irradiated to one of the liquid crystal cells during one frame period in the ferroelectric liquid crystal display. It is possible to drive only for one frame period because the response time of the ferroelectric liquid crystal to the voltage applied is considerably short in comparison with the liquid crystal in the nematic phase.

[0075] As illustrated in Fig. 15, because the realization of the tri-color of red, green and blue in a certain pixel cell is possible, the sub-pixel corresponding to each of the red, green and blue used in the conventional liquid crystal display is no longer necessary. Consequently, the resolution of the liquid crystal display according to the present invention increases three times as compared to the conventional liquid crystal display for the same

resolution.

[0076] Also, the red, green and blue color filters are not necessary in the ferroelectric liquid crystal display of the present invention because the backlight uses the primary three colors.

5 [0077] As a result of not using the color filter, light transmittance is increased by approximately 22%. In addition, because red, green and blue lights are sequentially irradiated only for the short time any deterioration in brightness can be compensated during the period the liquid crystal is capable of transmitting the light, i.e., while the required liquid crystal arrangement is sustained. For example, upon the synchronization of the turn-on time of the backlight and the liquid crystal arrangement time, the TFT can drive a ferroelectric liquid crystal having a relatively large spontaneous polarization. The VHR characteristics of the ferroelectric liquid crystal can be compensated by the increase of the size of the spontaneous polarization of the ferroelectric liquid crystal. Therefore, light efficiency can be improved by preventing the deterioration in brightness resulting from the VHR characteristics of the ferroelectric liquid crystal.

10 [0078] As described above, the ferroelectric liquid crystal display according to the present invention sequentially irradiates the red, green and blue lights during the short time when the liquid crystal has an arrangement in which the liquid crystal transmits light, thus preventing deterioration in the brightness resulting from the low voltage holding ratio of the ferroelectric liquid crystal and increasing the efficiency at the same time. The ferroelectric liquid crystal display according to the present invention uses the backlight corresponding to the red, green and blue so as not to require the sub-liquid crystal cell corresponding to each data signal of red, green and blue, and realizes as three times higher resolution as the conventional ferroelectric liquid crystal display with the same number of cells. Furthermore, 25 the ferroelectric liquid crystal display and the driving method thereof according to the present

invention does not use color filters so that the light transmittance can be increased by approximately 22% and can reduce the motion blurring phenomenon of a picture upon the display of a moving picture.

[0079] It will be apparent to those skilled in the art that various modifications and
5 variation can be made in the present invention without departing from the spirit or scope of the invention. Thus, it is intended that the present invention cover the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

4
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2